

## **Declaration of conformity in accordance with EU Directive 2014/68/EU (Pressure Equipment Directive)**

RITAG  
Ritterhuder Armaturen GmbH & Co. Armaturenwerk KG  
Sachsenring 30  
D-27711 Osterholz-Scharmbeck

RITAG sampling valves of types

**EPOS, BAP, BVP, BVP-S and BVP-AS**  
**Nominal diameter: DN32 – DN100, 1 ¼” – 4”**  
**Nominal pressure: PN6 – PN100, Class 150 – Class 600**

Category I, II and III, fluid group 2 (*valves for fluid group 1 see below!*)

Applied conformity assessment procedures:  
H (Full Quality Assurance)

Surveillance under the responsibility of

Lloyds Register Deutschland GmbH  
Am Sandtorkai 41  
20457 Hamburg

**CE** 0525

Applied harmonised norms and standards:

EN 12516, EN 1503, EN 10028, EN 10213, EN 10216, EN 10272, EN 10273, EN 12266,  
EN 13445, ISO 5208, AD 2000-Regelwerk, EN ISO 3834 and others.

Additionally applied norms and standards:  
ASME B16.34, API 598

Materials:

Ferritic, austenitic, duplex materials in cast and forged versions and non-ferrous metals

### **RITAG sampling valves for fluid group 1:**

The following RITAG sampling valves may be used for fluid group 1:

- Valves with sealing systems that correspond to the requirements of TA-Luft or comparable regulations. This is to be agreed/ordered separately.

### **RITAG sampling valves nominal diameter DN25 and smaller:**

The valves stated above correspond to the requirements of DGRL2014/68/EU in the same way, but are not indicated with **CE** in accordance with article 4 paragraph 3.

Osterholz-Scharmbeck, 30.05.2018

  
A. Nagel  
Technical Manager